


CODE: **AWO454** v1.1/III
 NAME: **EXPANDER2/SP/GRADE 3**



DESTINATION

SATEL:

- 1) 3x (CA10E, CA64E, SM, MST1)
- 2) 2x CA64 (EPS, O-OC, O-ROC, O-R, VGM-16, SR, ADR, ACC-KP, PS)+ CA10E (MST1)
- 3) CA64 (EPS, ADR, O-R, O-ROC, O-OC, VGM-16, SR, ACC- KP- PS)+ 2x (CA10E, CA64E, SM, MST1)
- 4) CA64 (PP, OPS- OC, OPS-R, OPS-ROC) + CA64 (EPS, ADR, O-R, O-ROC, O-OC, VGM16, SR, ACC-KP-PS)
- 5) CA64 PTSA

DSC:

- 1) 4x (4108, 5108, 6108, 5208, 5100, 4116)
- 2) (4108, 5108, 6108, 5208, 5100, 4116) + (4216, 4580, 5400, 5580)
- 3) 1x (4216, 4580, 5400, 5580)

PARADOX:

- 1) 3x (ZX4, ZX8, ZX8SP, HUB2, PGM4)
- 2) ADM2+ 2x (ZX4, ZX8, ZX8SP, HUB2, PGM4)

RISCO:

- 1) 2x (EZ8, EZ16, E04, E08)

ZKT_{Eco}:

- 1) C3 series: C3-100, C3-200

TECHNICAL DATA

External dimensions of the enclosure: W=297, H=203, D=67 D₁=16 [+/- 2mm]

External dimensions of the front panel: W₁=292, H₁=207 [+/- 2mm]

Weight netto/brutto: 1,62kg / 1,70kg [+/-0,1kg]

Operating conditions: II environmental class, -10°C+40°C

Operating environment: sheet steel DC01, thickness: 0,7mm, protection anticorrosion, color: RAL 9003

Destination: indoor

Tamper protection: 2 x microswitch: opening casing and detachment from the wall 0,5A@50V/DC max.
 NC- contacts

Closing: screwed x 2

Notes: distance from wall (mounting surface) - 15mm

Declaration, warranty: CE, CLC/TS 50131-1 Grade 3,
 2 year from the production date