

5M IR Bullet Camera with Heater

DC-T4533HRX

- Easy installation with DirectIP NVR
- 5MP (2592x1944) resolution
- Motorized Vari-focal lens (f = 3.0 - 13.5mm)
- micro SD/SDHC/SDXC
- Two-way audio
- Alarm in / out
- IK10 / IP67 supports
- Built-in heater
- PoE (IEEE 802.3af Class 3), 12V DC
- Day and night (ICR)
- True wide dynamic range (WDR)
- IR LED (Distance : 40m / 131.2 ft)
- 3-axis mechanical design for installation
- Supports ONVIF



SPECIFICATIONS


VIDEO	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Lens Type	Motorized Vari-focal
Focal Length	f = 3.0 - 13.5mm
Aperture	F1.4 - 3.2
Iris Control	DC IRIS
Angular Field of View	Wide : 91°(H) 66°(V) 120°(D) Tele : 31°(H) 23°(V) 38°(D)
Min. Illumination	Color : 0.1 lux @ F1.4 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB(True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10000), Anti-Flicker, Slow Shutter (1-1/5, 1/7.5, 1/15)
Day and Night	IR cut filter with auto switch
IR Distance (LEDs)	40m / 131.2 ft(6 ea)
Image Setting	Configurable Exposure, White Balance, Sharpness
Digital Noise Reduction	Configurable 2DNR/3DNR
Backlight Compensation	On / Off
Mirroring / Pivot	Horizontal / Vertical / Pivot
Image Stabilizer	Yes (DIS)
De-fog	On / Off
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Video Out	-
NETWORK	
	DirectIP Mode
Video Compression	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported
Bitrate Control	H.265 - VBR / CBR H.264 - VBR / CBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF
Max. Frame Rate	4:3 mode : 30ips : 2592 x 1944(WDR) 16:9 mode : 30ips : 2592 x 1456(WDR)
Supported Resolution	4:3 : 2592x1944, 1920x1440, 1280x960x 640x480 16:9 : 2592x1456, 1920x1080, 1280x720, 640x360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP Protocol, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTp, SMTp, FEN, mDNS, Upnp
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS, SSL Encryption
Remote Access Client	DirectIP NVR Connection, IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	Yes (Up to 100MB)
Recording Session Buffer (NLTRec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 256GB)
ALARM AND EVENT	
Trigger Event	Motion Detection, Alarm in, Audio Detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (With Image)
Audio In / Out	1 / 1
Alarm In / Out	1 / 1
ENVIRONMENTAL	
Vandal Proof Casing	IK10
Outdoor Ready	IP67, Heater
Operating Temperature	-40°C ~ +60°C (-40°F ~ +140°F) *Starting up at above -20°C (-4°F)
Operating Humidity	0% ~ 90%
ELECTRICAL	
Power Source	PoE (IEEE 802.3af Class 3), DC12V
Power Consumption	12V~, 0.78A, 9.36W PoE, IEEE 802.3af(Class 3) , 8W
Approvals	FCC, CE, KC
MECHANICAL	
Dimensions	Ø77mm X 244.1mm (Ø3" x 9.61")
Weight	0.84kg (1.85lb)

DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

