

# PSB series power supply

Enclosed, switch mode buffer power supply 13,8 V DC



CODE: **PSB-12V2A** v1.0/l  
TYPE: **PSB 13,8V/2A enclosed, switch mode buffer power supply**

EN

## Features of the power supply:

- DC 13,8 V/2 A uninterruptible power supply
- high efficiency 83%
- controlling of battery charging and maintaining
- protecting of battery against excessive discharging (UVP)
- battery charging current 0,5 A
- optional equipment: set of external LED indicators: PKAZ168, mounting plate DIN1
- battery output is full protected against short-circuit and reverse connection
- LED optical signalisation
- protections:
  - short-circuit protection SCP
  - over voltage protection OVP
  - surge protection
  - overload protection OLP
- warranty – 2 year from production date



## DESCRIPTION

Buffer-type power supply units are intended for continuous power supply to devices that require stabilised voltage of **12 V DC (+/-15%)**. The power supply provides a voltage of **U=13,8 V DC** with an output current of:

### Output current of 2 A + 0,5 A battery charging

In case of power voltage decay, prompt switching to battery supply occurs. The power supply unit is protected against a short circuit, an overload, a surge or over voltage protection.

## TECHNICAL DATA

|  |  |
|--|--|
| Supply voltage   | ~ 200 – 240 V; 0,4 A; 50/60 Hz   |
| Inrush current   | 40 A   |
| Supply power   | 35 W   |
| Efficiency   | 87%  |
| Output voltage (factory settings)  | 11-13,8 V DC – buffer operation<br>9,5-13,8 V DC – battery operation   |
| Output current   | 2,5 A  |
| Battery charging current   | 0,5 A  |
| Voltage adjustment range   | 13,5 – 14,4 V DC   |
| Current consumption by PSU during battery-assisted operation                 | approx. 35 mA  |
| Ripple voltage   | 100mV p-p max.   |
| Short-circuit protection SCP   | electronic, automatic recovery   |
| Overload protection OLP  | 105-150% PSU power, automatically recovered  |
| Overload protection (battery) OLP  | polymer fuse   |
| Surge protection   | varistors  |
| Overvoltage protection OVP   | >19 V (activation requires disconnecting the load or supply for about approx. 1 min.)  |
| Excessive discharge protection UVP   | U<9,5 V (± 5%) – disconnection of battery  |
| Optical signalisation  | LED green – indicates DC voltage at the power  |
| LED optical indication output (intended for optional indication set PKAZ168) | LED AC – presence of AC voltage<br>LED DC – presence of DC voltage on power supply output<br>LED CHARGE – battery charging process |
| Optional equipment   | A set for optical indication LED PKAZ168   |
| Operation conditions   | 2-nd environmental class, temperature: -10°C+40°C<br>relative humidity 20%...90%, without condensation                             |
| Dimensions   | L=110, W= 78, H=36 [±2mm]  |
| Net/gross weight   | 0,24 / 0,26 [kg]   |
| Protection class electric shock protection                                   | I (first) - requires a protective conductor  |
| Declarations, warranty   | CE, 2 year from the production date  |
| Connectors   | I/O PCB: 0,5 – 2,5 mm <sup>2</sup> (AWG 26 – 12)<br>output of optical signalization: 4 pins micromatch socket                      |
| Additional accessories   | Battery wires 6,3F – 45cm, ML062 angle muff (hole 5,2mm)   |

# PSB series power supply

Enclosed, switch mode buffer power supply 13,8 V DC



## Dimensions and fitting of the PSB-12V2A power supply

