

# WV-S65302-Z2G

2MP (1080p) 21x Outdoor PTZ Network Camera

## S-series PTZ camera with AI Engine



- 2MP (1080p) 1920x1080
- 21x optical zoom
- Intelligent Auto (with AI Engine)
- Super Dynamic 144dB
- Color night vision (0.003 to 0.045 lx)
- Durable Pan/Tilt gear mechanism
- IP66, IK10 certified
- Built-in FIPS 140-2 Level 3 Certified Secure Element with TPM functionality (EdgeLock® SE050F NXP® Semiconductors)
- NDAA Compliant



# SPECIFICATIONS

| Camera  |  |
|---|--|
| Image Sensor                                      | Approx. 1/2.8 type CMOS image sensor   |
| Minimum Illumination                              | Color : 0.045 lx (50IRE, F1.6, 1/30s)<br>Color : 0.003 lx (50IRE, F1.6, 16/30s)<br>BW : 0.017 lx (50IRE, F1.6, 1/30s)<br>BW : 0.0011 lx (50IRE, F1.6, 16/30s)                              |
| White Balance                                     | ATW1 / ATW2 / AWC  |
| Shutter Speed                                     | [60 fps Mode] 1/60 Fix to 1/10000 Fix,<br>[30 fps/15 fps mode] 1/30 Fix to 1/10000 Fix<br>[50 fps Mode] 1/50 Fix to 1/10000 Fix,<br>[25 fps/12.5 fps mode] 1/25 Fix to 1/10000 Fix         |
| Intelligent Auto                                  | On / Off   |
| Super Dynamic                                     | On / Off, The level can be set in the range of 0 to 31.  |
| Dynamic Range                                     | Max.144 dB (Super Dynamic : On, Level 31)  |
| Adaptive Black Stretch                            | The level can be set in the range of 0 to 255.   |
| Back light compensation / High light compensation | BLC (Back light compensation) / HLC (High light compensation) / Off<br>The level can be set in the range of 0 to 31 (only when Super dynamic / Intelligent Auto : Off)                     |
| Fog compensation                                  | On / Off, The level can be set in the range of 0 to 8<br>(only when Intelligent auto / auto contrast adjust : Off)   |
| Maximum gain (AGC)                                | The level can be set in the range of 0 to 11.  |
| Color/BW (ICR)                                    | Off / On / Auto1 / Auto2 / Auto3 (SCC)   |
| Digital Noise Reduction                           | The level can be set in the range of 0 to 255.   |
| Video Motion Detection (VMD)                      | On / Off, 4 areas available  |
| Scene Change Detection (SCD)                      | On / Off, 1 areas available  |
| Audio Detection                                   | On / Off   |
| AI Sound Classification                           | Gunshot, Yell, Vehicle horn, Glass break   |
| AI Analytics                                      | Yes  |
| Privacy Zone                                      | On / Off, Up to 32 zones available   |
| VIQS  | On / Off, Up to 8 zones available  |
| Image Stabilizer                                  | On / Off (available only in the 30 fps mode)   |
| Camera Title (OSD)                                | On / Off, Up to 40 characters (alphanumeric characters, marks)   |
| Focus Adjustment                                  | Auto focus   |
| Lens  |  |
| Optical zoom                                      | 21x (Motorized zoom / Motorized Focus)   |
| Extra zoom  | Max. 31x (21 to 31x : When resolution is 1280 x 720)   |
| Focal Length                                      | 4.0 - 84.6 mm {5/32 inches - 3-21/64 inches}   |
| Angular Field of View                             | [16 : 9 mode]<br>Horizontal : 3.7° (TELE) - 77° (WIDE), Vertical : 2.2° (TELE) - 44° (WIDE)<br>[ 4 : 3 mode]<br>Horizontal : 2.9° (TELE) - 58° (WIDE), Vertical : 2.2° (TELE) - 44° (WIDE) |
| Maximum Aperture Ratio                            | 1 : 1.6 (WIDE) - 1 : 4.5 (TELE)  |

|                                      |   |
|--------------------------------------|---|
| Focus Range                          | 1.5 m {50-1/16 inches} – ∞  |
| <b>DORI</b>                          |   |
| Detect (25ppm / 8ppf)                | Wide: 51.9m / 170.3 ft, Tele: 1293.8 m / 4244.9 ft  |
| Observe (62.5ppm / 19ppf)            | Wide: 20.8 m / 68.1 ft, Tele: 517.5 m / 1697.9 ft   |
| Recognize (125ppm / 38ppf)           | Wide: 10.4 m / 34.1 ft, Tele: 258.8 m / 849.0 ft  |
| Identify (250ppm / 76ppf)            | Wide: 5.2m / 17.0 ft, Tele: 129.4 m / 424.5 ft  |
| <b>System on Chip (SoC)</b>          |   |
| System on Chip (SoC)                 | Ambarella CV25M   |
| <b>Adjusting Angle</b>               |   |
| Adjusting Angle                      | Horizontal : 360° Endless Panning, Vertical : -15° to +195°, Yaw : 0°   |
| <b>Pan/tilt</b>                      |   |
| Panning Range                        | 360° Endless Panning  |
| Panning Speed                        | Manual: Approx. 0.065°/s – 150°/s<br>Preset: Up to approx. 500°/s   |
| Tilting Range                        | Operational -15 – +195°   |
| Tilting Speed                        | Manual: Approx. 0.065°/s – 150°/s<br>Preset: Up to approx. 500°/s (PoE+), Up to approx. 350°/s (DC12 V PoE)   |
| Preset Positions                     | 256 positions   |
| Auto Mode                            | Auto track/ Auto pan/ Preset sequence/ Patrol   |
| Self Return                          | 10 s/ 20 s/ 30 s/ 1 min/ 2 min/ 3 min/ 5 min/ 10 min/ 20 min/ 30 min/ 60 min  |
| <b>Browser GUI</b>                   |   |
| Camera Control                       | Brightness, AUX On / Off  |
| Audio                                | Mic (Line) Input : On / Off Volume adjustment : Low / Middle / High<br>Audio Output : On / Off Volume adjustment : Low / Middle / High  |
| GUI / Setup Menu Language            | English, Italian, French, German, Spanish, Portuguese, Russian, Chinese, Japanese   |
| Browser                              | Microsoft Edge, Firefox, Google Chrome  |
| <b>Network</b>                       |   |
| Network IF                           | 10 Base-T / 100 Base-TX, RJ45 connector   |
| Resolution H.265/ H.264 JPEG (MJPEG) | [16 : 9 mode (60 fps mode)] , [16 : 9 mode (30 fps mode)] ,<br>[16 : 9 mode (50 fps mode)] , [16 : 9 mode (25 fps mode)]<br>1920x1080, 1280x720, 640x360, 320x180<br>[4 : 3 mode (30 fps mode)], [4 : 3 mode (25 fps mode)]<br>1280x960, VGA, QVGA<br>[4 : 3 mode (15 fps mode)], [4 : 3 mode (12.5 fps mode)]<br>2048x1536 , 1280x960, VGA, QVGA |
| H.265/H.264                          | [Transmission Mode] Constant bit rate / VBR / Frame rate / Best effort<br>[Transmission Type] Unicast port (AUTO) / Unicast port (MANUAL) / Multicast   |
| JPEG                                 | [Image Quality] 10 steps  |
| Smart Coding                         | GOP (Group of pictures) control:<br>Off/ Low (Variable GOP 1s-8s)/ Mid (Variable GOP 4s-16s)/<br>Advanced(Fixed GOP 60s w/1s key-frame)/<br>Frame rate control (Variable GOP 4s-16s with frame rate control)<br>*Advanced and Frame rate control are only available with H.265.<br>Smart Coding: Auto VIQS: On/Off                                |
| Audio Compression                    | G.726 (ADPCM) : 16 kbps / 32 kbps<br>G.711 : 64 kbps<br>AAC-LC : 64 kbps / 96 kbps / 128 kbps   |
| Audio Transmission Mode              | Off / Mic (Line) input / Audio output / Interactive (Half duplex) / Interactive (Full duplex)   |

|                                   |  |
|-----------------------------------|--|
| Supported Protocol                | IPv6 : TCP/IP, UDP/IP, HTTP, HTTPS, SSL/TLS, SMTP, DNS, NTP, SNMPv1/v2/v3, DHCPv6, RTP, MLD, ICMP, ARP, IEEE 802.1X, DiffServ, SFTP, MQTT, LLDP<br>IPv4 : TCP/IP, UDP/IP, HTTP, HTTPS, SSL/TLS, RTSP, RTP, RTP/RTCP, SMTP, DHCP, DNS, DDNS, NTP, SNMPv1/v2/v3, UPnP, IGMP, ICMP, ARP, IEEE 802.1X, DiffServ, SRTP, SFTP, MQTT, NTCIP   |
| No. of Simultaneous Users         | Up to 14 users (Depends on network conditions)   |
| Secure                            | FIPS 140-2 level 3 Certified Secure Element (NXP® EdgeLock® SE050F), Device Certificate GlobalSign® pre-installed, User authentication, Host authentication, HTTPS, 802.1X Support, Data encryption  |
| SDXC/SDHC/SD Memory Card (Option) | H.265 / H.264 recording :<br>Manual REC / Alarm REC (Pre/Post) / Schedule REC / Backup upon network failure<br>JPEG recording :<br>Manual REC / Alarm REC (Pre/Post) / Backup upon network failure<br>Compatible SDXC/SDHC/SD Memory Card :<br>microSDXC memory card : 64 GB, 128 GB, 256 GB, 512 GB<br>microSDHC memory card : 4 GB, 8 GB, 16 GB, 32 GB<br>microSD memory card : 2 GB |
| Mobile Terminal Compatibility     | iPad, iPhone (iOS 8.0 or later), Android™ terminals  |
| ONVIF® Profile                    | G / M / S / T  |

| Alarm         |  |
|---------------|--|
| Alarm Source  | 3 terminals input, VMD alarm, Command alarm, Audio detection alarm   |
| Alarm Actions | SDXC/SDHC/SD memory recording, E-mail notification, HTTP alarm notification Indication on browser, TCP alarm notification output |

| Input/Output           |   |
|------------------------|---|
| Audio Input            | ø3.5 mm stereo mini jack<br>For microphone input : Recommended applicable microphone : Plug-in power type (Sensitivity of microphone : -51 dB to -38 dB (0 dB=1 V/Pa, 1 kHz))<br>Input impedance : Approx. 2 kΩ (unbalanced)<br>Supply voltage : 2.5 V ±0.5 V<br>For line input : Input level : Approx. -10 dBV |
| Audio Output           | ø3.5 mm stereo mini jack (monaural output)<br>Output impedance : Approx. 600 Ω (unbalanced)<br>Output level : -20 dBV   |
| External I/O Terminals | ALARM IN 1 (Alarm input 1/ Black & white input/ Auto time adjustment input) (x1)<br>ALARM IN 2 (Alarm input 2/ ALARM OUT) (x1), ALARM IN 3 (Alarm input 3/ AUX OUT) (x1)  |

| General                            |   |
|------------------------------------|---|
| Safety                             | UL (UL62368-1), c-UL (CSA C22.2 No.62368-1), CE, IEC62368-1   |
| EMC                                | FCC (Part15 ClassA), ICES-003 Issue 7 ClassA, EN55032 ClassA, EN55035   |
| Power Source and Power Consumption | DC12 V, PoE (IEEE802.3af), PoE+ (IEEE802.3at)<br>DC12 V: 1.3 A / Approx.15.6 W<br>PoE DC 48 V: 270 mA / Approx.12.95 W (Class 0 device)<br>PoE+ DC 54 V: 340 mA / Approx.18.4 W(Class 4 device) |
| Ambient Operating Temperature      | -30 °C to +55 °C (-22 °F to +131 °F)<br>(Power On range : -20 °C to +55 °C {-4 °F to +131 °F})<br>Maximum temperature according to NEMA TS2(2.2.7) : 74 °C(165 °F)                              |
| Ambient Operating Humidity         | 10 to 100 % (no condensation)   |
| Anti-Condensation System           | Temish element  |
| Water and Dust Resistance          | IP66, IEC60529 measuring standard compatible, Type 4X(UL50E), NEMA 4X compliant   |
| Shock Resistance                   | IK10 (IEC 62262)  |
| Other standard support             | NEMA TS2(2.2.7-2.2.9)   |
| Dimensions                         | ø165 mm x 153 mm (H) {ø6-1/2 inches x 6-1/32 inches (H)}  |
| Mass (Approx.)                     | Approx. 1.7 kg {3.75 lbs.}  |
| Finish                             | Main body : Aluminum die cast, Black polycarbonate resin, i-PRO white<br>Outer fixing screws : Stainless steel (Corrosion-resistant treatment)<br>Dome section : Polycarbonate resin, Smoke     |

## NOTES

### Important

- Safety Precautions : Carefully read the Basic Information, Installation Guide and Operating Instructions before using this product.
- i-PRO Co., Ltd. cannot be held responsible for the performance of the network and/or other manufacturers' products used on the network.
- Masses and dimensions are approximate.
- Specifications are subject to change without notice.

### Trademarks and registered trademarks

- iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. – Android is a trademark of Google LLC.
- ONVIF is a trademark of ONVIF, Inc.
- All other trademarks identified herein are the property of their respective owners

©i-PRO Co., Ltd All rights reserved / November 2022

## OPTIONAL ACCESSORIES

Select a compatible accessory

[Accessory Selector \(i-pro.com\)](http://i-pro.com).



WV-QDC502G  
Dome Cover



WV-QWL500-W  
Mount Bracket



WV-QJB500-W  
Mount Bracket



WV-QWL501-W  
Mount Bracket



WV-QSR501-W  
Mount Bracket



WV-QSR501F1-W  
Mount Bracket



WV-QSR501M1-W  
Mount Bracket



WV-QCL101-W  
Mount Bracket



WV-QCL501-W  
Mount Bracket



WV-QJB501-W  
Base Bracket



WV-QEM504-W  
Ceiling Mount Bracket



WV-QJB504-W  
Base Bracket



WV-QSR501F-W  
Mount Bracket



WV-QSR501M-W  
Mount Bracket



WV-QCA501A  
I/O Cable

# APPEARANCE

